




Summer on the Sound Quilt (Q-029A)



Fabric requirements



Fabric A: 6141201 #1
5/8 yard



Fabric B:
214-0003 Au Naturel
1/2 yard



Fabric C: 6141205 #1
5/8 yard



Fabric D: 6141202 #1
2/3 yard



Fabric E: 6141204 #3
2/3 yard



Fabric F: 214-0001 White
2 yards



Fabric G:
214-0035 Spearmint
1/8 yard



Fabric H (binding):
6141205 #1
1/2 yard



Suggested Backing:
6141202 #1
4 yards

Exclusive Quilt Design by Stephanie Palmer of Late Night Quilter for Camelot Fabrics.
Fabric collection: It's a Bird's Life by Heather Rosas for Camelot Fabrics



Blog, Facebook, Twitter @CamelotFabrics
Pinterest, YouTube & Instagram @Camelot_Fabrics
camelotfabrics.com • camelotfabricsblog.com
Toll-Free: 1-800-361-4120 • 514-382-2400
info@camelotfabrics.com • www.camelotfabrics.com

Finished Size: 63" x 63"

OTHER TOOLS & SUPPLIES

- 2 yards of extra-wide quilt batting (at least 66" wide)
- sewing machine & coordinating thread
- rotary cutter & mat
- fabric shears
- straight pins
- fabric marker
- straight edge ruler & measuring tape

NOTES

- For best results, read through all the instructions before starting.
- Please wash, dry & iron your fabric before beginning, and trim selvages.
- Unless otherwise directed, sew all seams with an accurate 1/4" allowance and the fabrics' Right Sides together, and press seams open as you go.
- WOF = Width of Fabric (42")
- HST = Half Square Triangle
- For block arrangement and fabric placement throughout the tutorial, please refer to the quilt illustration on Page 1.

CUTTING

Fabric A

Cut (1) 7" x WOF strip - sub-cut (6) 7" squares.


Cut (1) 10-1/2" x WOF strip - sub-cut (1) 10-1/2" square & (2) 7" squares.

Fabric B

Cut (3) 3-5/8" x WOF strips - sub-cut (32) 3-5/8" squares.

Cut (1) 4" x WOF strip - sub-cut (4) 3-1/2" squares & (2) 4" squares.

Cut each 4" square in half through the diagonal as shown, to make (4) half-square triangles.



Fabric C

Cut (3) 3-3/8" x WOF strips - sub-cut (32) 3-5/8" squares.

Cut (1) 3-1/2" x WOF strip - sub-cut (8) 4-1/2" x 3-1/2" rectangles.

Cut (1) 4" x WOF strip - sub-cut (2) 4" squares & (4) 3-1/2" squares.

Cut each 4" square in half through the diagonal.

Fabric D

Cut (3) 3-5/8" x WOF strips - sub-cut (32) 3-5/8" squares.

Fabric E

Cut (2) 5-7/8" x WOF strips - sub-cut (14) 5-7/8" squares.

Cut (1) 5-7/8" x WOF strip - sub-cut:

(2) 5-7/8" squares

(4) 4" squares - cut each 4" square in half through the diagonal.

Cut (1) 3-1/2" x WOF strip - sub-cut (8) 3-1/2" squares.

Fabric F

Cut (4) 5" x WOF strips - sub-cut (32) 5" squares.

Cut (2) 5-7/8" x WOF strips - sub-cut (14) 5-7/8" squares.

Cut (1) 5-7/8" x WOF strip - sub-cut:

(2) 5-7/8" squares

(4) 4-1/2" squares

(8) 1-1/2" squares.

Cut (12) 1-3/4" x WOF strips - sub-cut (24) 18-1/2" x 1-3/4" rectangles (Sashing)

Cut (7) 1-1/2" x WOF strips (Borders)

Fabric G

Cut (1) 1-3/4" x WOF strip - sub-cut (16) 1-3/4" squares (Cornerstones)


Fabric H

Cut (7) 2-1/2" x WOF strips (Binding)

Backing

Cut (2) 72" x WOF rectangles.

PICKET FENCES BLOCKS



1. Sew a 3-5/8" Fabric B square to a 3-5/8" Fabric C square as shown.

Make (4)




2. Sew a 3-5/8" Fabric D square to either end of (2) B/C rectangular units as shown.


Make (2)



3. Sew (2) B/C units to the left-hand & right-hand sides of a 7" Fabric A square as shown.



4. Sew the (2) 4-square units from Step 2 to the top & bottom of the 7" Fabric A square.




5. Place a 5-7/8" Fabric F square on a 5-7/8" Fabric E square, Right Sides together. Draw a diagonal line through the center of the Fabric F square, and sew 1/4" from the line on both sides as shown.

Cut on the center line to make (2) HST units.

6. Place (2) HST units together as shown, Right Sides together, with the Fabric F side of (1) HST over the Fabric E side of the other HST.

Make a pair of HSTs in the same manner as you made the first pair, with the seams running at 90° to the seams of the original HSTs.





7. Square up the HSTs to 5-1/4" square, and cut each one in half through the diagonal as shown. You should now have (4) quarter-square triangles.

Make (64) - from (16) pairs (E & F) of 5-7/8" squares.

8. Sew (2) quarter-square triangles to (2) adjacent sides of a 5" Fabric F square as shown, to form a corner unit of the Picket Fences Block.

Make (4)






9. Sew the each corner unit to (1) side of the square unit from Step 4 as shown, along the corner unit's longest edge.


Make (7) more Picket Fences blocks - (8) blocks total.

WHEEL OF FORTUNE BLOCK


There are (5) different types of sub-blocks within the Wheel of Fortune block:




(1) Center Square




(4) Corner squares.



(4) Hourglass squares.





(4) left-hand rectangles & (4) right-hand rectangles.




1. Place a 3-1/2" Fabric B square against one corner of the large Fabric A square, and draw a diagonal line through its center as shown. Sew along the diagonal line and trim 1/4" outside the seam.

Repeat for the remaining (3) corners of the Fabric A square, to complete the Center square.




2. Place a 3-1/2" Fabric C square against one corner of a 4-1/2" Fabric F square, Right Sides together, and draw a diagonal line through its center as shown. Sew along the diagonal line and trim 1/4" outside the seam.


Make (4).



3. Place a 3-1/2" Fabric E square against the bottom edge of a 3-1/2" x 4-1/2" Fabric C rectangle, and draw a diagonal line from its top left corner to its bottom right corner as shown. Sew along the diagonal line and trim 1/4" outside the seam.






4. Place a 1-1/2" Fabric F square at the top left corner of the Fabric C rectangle, draw a diagonal line and sew it in place as you did with the Fabric E square.



5. Repeat Steps 3-4, placing the Fabric E & F squares against the right-hand side of the Fabric C rectangle.


Make (4) of each.



6. Sew a Fabric C triangle to a Fabric E triangle and a Fabric B triangle to another triangle E triangle, as shown.


7. Sew the (2) resulting triangles together along their longest edges, as shown.

Make (4) Hourglass squares.




8. Sew a left- and right-hand rectangle to either side of an Hourglass square as shown

Make (4) rows.



9. Sew a corner square to each end of (2) rows, as shown.

Make (2).



10. Sew the (2) short rows to opposite sides of your center square. Sew the (2) longer rows to the top & bottom of the center square.

This completes the Wheel of Fortune Block.

QUILT TOP

1. Sew (4) 1-3/4" Fabric G squares together with (3) 18-1/2" x 1-3/4" Fabric F rectangles, alternating between the fabrics as shown, to make a Sashing strip.



Make (4) strips.

2. Referring to the Assembly Layout on the final page, sew the (9) Blocks together in rows of (3) blocks, with a 1-3/4" x 18-1/2" Sashing rectangle between each one and at both ends of each row.

3. Sew the (3) rows together, with a Sashing strip between each row.

This completes the quilt Center.

4. Join the 1-1/2" Fabric F Border strips end-to-end. You will cut each Border piece from this strip.

5. Measure the quilt center's height through the middle, and cut (2) side borders to this length. Sew them to the left- and right-hand sides of the quilt center.

6. Measure the quilt center's width through the middle, including the side borders. Cut top & bottom borders to this length, and sew them to the top & bottom of the quilt center.

FINISHING THE QUILT

1. Join the Fabric H binding strips end-to-end, and press them to make double-fold binding.

2. Join the (2) Backing rectangles along (1) pair of 72" edges.

Layer your quilt top, batting & backing. Baste & quilt as desired, trim the excess batting & backing, and bind with Fabric H.



ASSEMBLY LAYOUT

